





AC Dull Gold Laminated Foil ** BP-164 ** 40# liner

Item#: 0041739

TRIMLESS PROGRAMS			
Dist. Ctr	Length	Min. Width	Core
Troy, Ohio	2.5 K	3"	3"
Troy, Ohio	5 K	3"	3"
New York	5 K	3"	3"
Los Angeles	5 K	3"	3"
Los Angeles	2.5 K	3"	3"
	Dist. Ctr Troy, Ohio Troy, Ohio New York Los Angeles	Dist. CtrLengthTroy, Ohio2.5 KTroy, Ohio5 KNew York5 KLos Angeles5 K	Dist. CtrLengthMin. WidthTroy, Ohio2.5 K3"Troy, Ohio5 K3"New York5 K3"Los Angeles5 K3"

Facestock: AC Dull Gold Laminated Foil

A .000285 mil foil laminated to a 55# coated base paper. This foil has an acrylic top coat specifically designed for use with waterand solvent-based inks.

Typical Value

Basis Weight:

73#/3300 ft

Caliper:

3.5mils

Tensile MD/CD:

35 / 21

Tear MD/CD:

64 / 68 grams

Adhesive: BP-164

A general purpose hot melt adhesive with excellent quick-stick properties. This adhesive exhibits excellent adhesion to a broad range of packaging surfaces and has improved die cutting and stripping attributes compared to other hot melt rubber based adhesives.

Typical Value

Coat Weight:

14#/3300 ft²

Coat Weight:

20.72 grams/m²

Caliper:

.6 mils

Adhesion to Stainless Steel, oz. (90° Peel):

63

Loop Tack, oz.:

97

Service Temperature:

-50 to 150 °F

Minimum Application Temperature:

40 °F

Shear (1000g):

456 minutes



Release Liner:40# liner		A bleached, calendered liner featuring excellent die cutting and stripping characteristics. Recommended for use in roll-to-roll applications.		
D. C. W. C.	Typical Value	·		
Basis Weight:	41 #/3000 ft ²			
Caliper:	2.5 mils			
Tensile MD/CD:	34 / 21 #/inch			
Tear MD/CD:	34 / 36 grams			
Opacity:	69 max%			
Total Product Caliper: 6.6mils Product Basis Weight Per MMSI: 278.11# Shelf Life: 12month(s) when stored at 72° F, 50% RH		For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.		
_				
2005 100 100 100 100 100 100 100 100 100				