





AC Bright Silver Laminated Foil ** BP-164 ** 40# liner

Item#: 0041779

		TRIMLESS PROGRAMS			
Name (In Case of M	Dist. Ctr	Length	Min. Width	Core	
	Troy, Ohio	2.5 K	3"	3"	
	Troy, Ohio	5 K	3"	3"	
	Chicago	5 K	3"	3"	

Facestock: AC Bright Silver Laminated Foil

A .000285 mil foil laminated to a 55# coated base paper. This foil has an acrylic top coat specifically designed for use with waterand solvent-based inks.

EDIMERCO DE CONTRE

Typical Value

Basis Weight:

Caliper:

Tensile MD/CD:

Tear MD/CD:

73#/3300 ft

3.5mils

35 / 21

64 / 68grams

Adhesive: BP-164

A general purpose hot melt adhesive with excellent quick-stick properties. This adhesive exhibits excellent adhesion to a broad range of packaging surfacesand has improved die cutting and stripping attributes compared to other hot melt rubber based adhesives.

Typical Value

Coat Weight:

14#/3300 ft²

Coat Weight:

20.72 grams/m²

Caliper:

.6 mils

Adhesion to Stainless Steel, oz. (90° Peel):

63 97

Loop Tack, oz.: Service Temperature:

-50 to 150 °F

Minimum Application Temperature:

40 °F

Shear (1000g):

456 minutes



Release Liner:40# liner	iner:40# liner A bleached, calendered liner featuring excellent die cutting and stripping characteristics. Recommended for use in roll-to-roll applications.	
Dorig Woight	Typical Value 41 #/3000 ft ²	
Basis Weight: Caliper:	2.5 mils	
Tensile MD/CD:	34 / 21 #/inch	
Tear MD/CD:	34 / 36 grams	
Opacity:	69 max%	
Total Product Caliper: 6.6mils Product Basis Weight Per MMSI: 278.11# Shelf Life: 12month(s) when stored at 72° F, 50% RH		For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative
terri		