



Let Us Label You

2.6 mil TC White Label-Lyte® ** SFA™ ** 40# liner

Item#: 0042311

----- **TRIMLESS PROGRAMS** -----

Dist. Ctr	Length	Min. Width	Core
Troy, Ohio	2.5 K	3"	3"
Troy, Ohio	5 K	3"	3"
Troy, Ohio	10 K	4"	3"
Atlanta	2.5 K	3"	3"
Atlanta	5 K	3"	3"
Atlanta	10 K	4"	3"

Facestock: 2.6 mil TC White Label-Lyte®

A white, multi-layer, biaxially-oriented polypropylene film that is top-coated for ink receptivity.

Typical Value

Basis Weight:	33.2#/3300 ft
Caliper:	2.6mils
Tensile MD/CD:	12,600 / 22,200PSI
Elongation @ Break MD/TD:	180 / 45%
Opacity:	88%

Adhesive: SFA™

A clear, general purpose, emulsion acrylic permanent adhesive designed for applications with film facestocks. SFA exhibits excellent ultimate adhesion to polyethylene, polypropylene and glass. Well suited for small, cylindrical labeling and is glove friendly.

Typical Value

Coat Weight:	13#/3300 ft ²
Coat Weight:	19.24 grams/m ²
Caliper:	.6 mils
Adhesion to Stainless Steel, oz. (90° Peel):	27
Loop Tack, oz.:	33
Service Temperature:	-40 to +200 °F
Minimum Application Temperature:	40 °F
Shear (1000g):	450 minutes



Let Us Label You

Release Liner:**40# liner**

A bleached, calendered liner featuring excellent die cutting and stripping characteristics. Recommended for use in roll-to-roll applications.

Basis Weight:

Typical Value

41 #/3000 ft²

Caliper:

2.5 mils

Tensile MD/CD:

34 / 21 #/inch

Tear MD/CD:

34 / 36 grams

Opacity:

69 max%

Total Product Caliper:5.7mils

Product Basis Weight Per MMSI: 192.21#

Shelf Life:12month(s) when stored at 72° F, 50% RH

For application recommendations call 877-210-5104

For samples or other questions please call your Sales Representative.