



Let Us Label You

ScanTherm™ NTC ** A-BC-20™ ** 40# liner

Item#: 0045631

----- **TRIMLESS PROGRAMS** -----

Dist. Ctr	Length	Min. Width	Core
Troy, Ohio	2.5 K	3"	3"
Troy, Ohio	5 K	3"	3"
Troy, Ohio	10 K	4"	3"

Facestock: ScanTherm™ NTC

A direct thermal facestock designed for short-duration labeling. As the sheet does not have a grease resistant top coating, it is not suitable for applications requiring water or chemical resistance (solvents, oils, fats, or similar substances).

Typical Value

Basis Weight:	51#/3300 ft
Caliper:	3.3mils
Tensile MD/CD:	35 / 16
Gloss:	9%
Tear MD/CD:	43 / 44grams
Opacity:	92%
Sheffield Smoothness:	25 SFU
Parker Print:	1.5 microns
Brightness:	87%

Adhesive: A-BC-20™

A-BC-20 is a light coat weight of BC-20 cold temperature permanent. It is a hot melt, rubber based pressure adhesive featuring excellent adhesion to a variety of packaging materials and other substrates over a wide temperature range. In field processing, A-BC-20 standard constructions have displayed excellent die cutting and stripping characteristics.

Typical Value

Coat Weight:	12#/3300 ft ²
Coat Weight:	17.76 grams/m ²
Caliper:	.5 mils
Adhesion to Stainless Steel, oz. (90° Peel):	29 oz
Loop Tack, oz.:	52 oz
Service Temperature:	-50 to 145 °F
Minimum Application Temperature:	10 °F
Shear (1000g):	58 minutes



A bleached, calendered liner featuring excellent die cutting and stripping characteristics. Recommended for use in roll-to-roll applications.

Typical Value

Basis Weight:	41 #/3000 ft ²
Caliper:	2.5 mils
Tensile MD/CD:	34 / 21 #/inch
Tear MD/CD:	34 / 36 grams
Opacity:	69 max%

Total Product Caliper:6.3mils
Product Basis Weight Per MMSI: 227.58#
Shelf Life:12month(s) when stored at 72° F, 50% RH

*For application recommendations call 877-210-5104
For samples or other questions please call your Sales Representative.*